

INDEURO

CERAMIC

PORCELAIN
STONEWARE

30X60CM



Surface: Matt




E1-1009

PORCELAIN
STONEWARE

30X60CM

Random Face


Surface: Matt



E1-1009

**PORCELAIN
STONEWARE**

30X60CM

  IDEALLY SUITABLE FOR
MATT WALL | EXTERIOR WALL APPLICATION


TECHNICAL SPECIFICATION

r. No.	Property	GROUP B1a - ISO 13006 , STANDARDS	INDEURO Value	Test Method
1	Deviation in length	± 0.6%	± 0.1%	ISO 10545 -2
2	Deviation in THICKNESS	± 5%	± 0.4%	ISO 10545-2
3	Straightness of sides	± 0.5%	± 0.1%	ISO 10545-2
4	Rectangularity	± 0.6%	± 0.1%	ISO 10545-2
5	Surface flatness	± 0.5%	± 0.15%	ISO 10545-2
6	Surface quality (%)	A minimum of 95% of the tiles shall be free from visible defects that would impair the appearance of	98% free from Visible Defects	ISO 10545-2
7	Modulus of rupture	> 35 N/mm ³	40 N/mm ¹	ISO 10545-4
8	Breaking Strength	> 1300 N	> 2000 N	ISO 10545-4
9	Water absorption	< 0.5%	-< 0.08%	ISO 10545-3
10	Stain resistance	Stain proof	Stain proof	ISO 10545-14
11	Chemical resistance	No damage	No damage	ISO 10545-13
12	Thermal expansion	< 9 x 10 ⁶	< 6x10 ⁶	ISO 10545-8
13	Moisture expansion	Nil	Nil	ISO 10545-10
14	Thermal shock resistance	No damage	No damage	ISO 10545-9
15	Resistance to surface abrasion	Manufacturer to state abrasion class	PEI class 5	ISO 10545-7

E1-1009

**PORCELAIN
STONEWARE**

30X60CM

  IDEALLY SUITABLE FOR
MATT WALL | EXTERIOR WALL APPLICATION