

INDEURO

CERAMIC



GLAZED POLISHED
PORCELAIN TILES
60X60CM

Random Faces



POLISHED FLOOR

IDEALLY SUITABLE FOR
FLOOR APPLICATION

GLOBAL STATUARIO

GLAZED POLISHED PORCELAIN TILES

60X60CM

Random Faces



GLOBAL STATUARIO

GLAZED POLISHED
PORCELAIN TILES

60X60CM



POLISHED



FLOOR

IDEALLY SUITABLE FOR
FLOOR APPLICATION

FLOOR TILES

| r. No. | CHARACTERISTIC | STANDARD AS PER ISO -13006/EN14411 GROUP BILL | INDEURO Value | Test Method |
|--------------------------------------|-----------------------------|---|-----------------------------|--------------|
| REGULATORY PROPERTIES | | | | |
| 1 | Deviation in length & width | ± 0.5% | ±0.3% | ISO-10545-2 |
| 2 | Deviation in thickness | ± 5.0% | ± 4.0% | ISO-10545-2 |
| 3 | Straightness in sides | ± 0.5% | ± 0.1% | ISO-10545-2 |
| 4 | Rectangularity | ± 0.5% | ± 0.1% | ISO-10545-2 |
| 5 | Surface flatness | ± 0.5% | ± 0.2% | ISO-10545-2 |
| 6 | Color Difference | Unlterned | No change | ISO-10545-16 |
| 7 | Glossiness | As per mfg. | Min 90% | GLOSSOMETER |
| STRUCTURAL PROPERTIES | | | | |
| 8 | Water absorption | < 0.50% | < 0.05% | ISO-10545-3 |
| 9 | Apparent density | > 2.0 g/cc | > 2.10 g/cc | DIN 51082 |
| MASSIVE MECHANICAL PROPERTIES | | | | |
| 10 | Modulus of repture | Min. 35 N/mm2 | Min. 40 N/mm2 | ISO-10545-4 |
| 11 | Breaking strength | Min. 1300 N | Min. 2000 N | ISO-10545-4 |
| 12 | Impact resistance | As per mfg. | Min. 0.55 | ISO-10545-5 |
| SURFACE MECHANICAL PROPERTIES | | | | |
| 13 | Surface abrasion resistance | As per mfg. | Min. Class-3 | ISO-10545-7 |
| 14 | MOH's hardness | As per mfg. | Min. 6 | EN 101 |
| THERMO HYGROMRTRIC PROPERTIES | | | | |
| 15 | Frost Resistance | No damage | No damage | ISO-10545-12 |
| 16 | Thermal Shock Resistance | No damage | No damage | ISO-10545-9 |
| 17 | Moisture Expansion | Nil | Nil | ISO-10545-10 |
| 18 | Thermal Expansion(COE) | Max. 9.0 x 10 ⁻⁶ | Max. 6.5 x 10 ⁻⁶ | ISO-10545-8 |
| 18 | Crazing Resistance | As per mfg. | Min. 10 Cycle | ISO-10545-11 |
| CHEMICAL PROPERTIES | | | | |
| 19 | Chemical Resistance | No damage | No damage | ISO-10545-13 |
| 20 | Stain Resistance | Resistant | Resistant | ISO-10545-14 |
| SAFETY PROPERTIES | | | | |
| 21 | Slip Resistance | As per mfg. | > 0.40 | ISO-10545-17 |
| 22 | Fire Resistance | As per mfg. | Fireproof | N.A. |

GLOBAL STATUARIO

GLAZED POLISHED
PORCELAIN TILES

60X60CM

